



Ultra- Spill Deck Fluorinated Model P4

Product Data Sheet

Item Number: 1325

Item Name: Ultra- Spill Deck Fluorinated Model P4

Load Capacity UDL: 6,000 lbs. (2722kg)

Sump Capacity: 44 Gallons (167L)

Item #	Color	Amount	Length	Width	Height	Weight	QTY/ Pallet
1325	Blue/Black	1 Each	52" (1321mm)	52" (1321mm)	5 ¾" (146mm)	62 lbs. (28 kg)	20

Description: A fluorinated polyethylene sump with deck surface large enough to store four 55- Gallon drums. In the event of a leak, fluid is contained in the sump preventing contamination to surrounding environment. Capable of withstanding chlorinated and other aggressive solvents.

Application: For storage of both steel and polyethylene drums and smaller containers which need to meet containment regulations and/or for general housekeeping purposes.

Product Features: The Ultra-Spill Deck Fluorinated Model P4 helps you comply with containment regulations while storing steel and poly drums containing chlorinated or aggressive solvents. Capture leaks, drips, and spills to keep floors dry and workers safe.

- Molded-in sump catches leaks, drips and spills to help you comply with regulations and keep your storage area clean and safe.
- Fluorination gas treatment allows this unit to survive in environments with chlorinated or aggressive chemicals that normal LLDPE is not compatible with.
- Low profile design reduces safety and handling concerns found with taller spill containment pallets.
- Linear Low-density Polyethylene construction resists UV rays, rust, corrosion and most chemicals for long trouble-free life of the product.
- Removable grates – makes clean-up quick and easy.
- Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175 when connected with other Spill Decks.

Composition: 100% polyethylene with UV inhibitors and fluorination gas treatment.

Helps you comply with: 40 CFR 112.7 and 40 CFR 264.175

Additional Specifications: Grate dimensions 2- 48"x24"

Disclaimers: [Flammables Notice:](#) If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources.