



ULTRATECH
INTERNATIONAL, INC.

BMP

SWPPP

LEED

Ultra-Dewatering Bag[®]

Contain sediment pumped out during dewatering operations

Draining swampy or low-lying areas is a common occurrence in construction. Unfortunately, pumping out the water from these areas also removes a lot of dirt, silt, mud, and debris along with the water. These contaminants can cause problems if they are simply discharged into a storm drain.

The Ultra-Dewatering Bag provides an economical and effective solution. By pumping water into the bag, silt, dirt, sand and other pollutants are trapped and filtered so only water escapes to the ground below or nearby storm drains.

NOTE: To increase the efficiency of filtration, the bag can be placed on an aggregate or haybale bed to maximize water flow through the surface area of the bag.



Product Highlights

- + Standard and custom sizes available.
- + Accommodates up to 4-inch discharge hose.
- + Optional hose connector (Part# 9739) available
 - makes connecting and disconnecting Ultra-Dewatering Bags quick and easy.
- + Material: 8 oz. Non Woven

Ultra-Dewatering Bag

Part#	Model	Dimensions ft. (m)	Capacity cu. ft (L)	Weight Lbs. (Kg)
9729-OS	Dewatering Bag 3 x 4	3 x 4 (0.9 x 1.2)	12 (340)	2.0 (0.9)
9720-OS	Dewatering Bag 4 x 6	4 x 6 (1.2 x 1.8)	24 (680)	4.0 (1.8)
9724-OS	Dewatering Bag 6 x 6	6 x 6 (1.8 x 1.8)	36 (1,019)	5.0 (2.3)
9721-OS	Dewatering Bag 6 x 9	6 x 9 (1.8 x 2.7)	54 (1,529)	5.0 (2.3)
9723-OS	Dewatering Bag 8 x 8	8 x 8 (2.4 x 2.4)	64 (1,812)	7.0 (3.2)
9725-OS	Dewatering Bag 10 x 15	10 x 15 (3.0 x 4.6)	150 (4,247)	17.0 (7.1)
9727-OS	Dewatering Bag 15 x 15	15 x 15 (4.6 x 4.6)	225 (6,371)	26.0 (11.8)