



ULTRATECH
INTERNATIONAL, INC.

Ultra-Containment Berms®



Ultra-Containment Berm® Foam Wall Model

Low profile design is perfect for equipment maintenance and portable drum containment

Ultra-Containment Berm® Foam Wall Models

Low profile design is perfect for equipment maintenance and portable drum containment. Low, 4" sidewall contains spills - keeps plant floors and soil free from contamination.



8583

12' x 50' rolled up

Copolymer 2000™ Part#	PVC 22 oz. Part#	Dimensions ft. (m) Wall Height: 4 in. (102 mm)	Containment Capacity gal. (L)	Copolymer 2000 Weight lbs. (kg)	PVC 22 oz. Weight lbs. (kg)
8570	8460	4 x 6 (1.2 x 1.8)	59 (223)	27.0 (12.0)	21.0 (9.5)
8571	8461	8 x 8 (2.4 x 2.4)	159 (602)	45.0 (20.0)	40.0 (18.0)
8572	8470	10 x 10 (3.0 x 3.0)	249 (943)	61.0 (28.0)	51.0 (23.0)
8573	8471	10 x 20 (3.0 x 6.1)	498 (1,885)	101.0 (46.0)	83.0 (38.0)
8574	8472	10 x 30 (3.0 x 9.1)	748 (2,832)	137.0 (62.0)	118.0 (54.0)
8575	8473	10 x 40 (3.0 x 12.2)	997 (3,774)	177.0 (80.0)	150.0 (68.0)
8576	8474	10 x 50 (3.0 x 15.2)	1,246 (4,717)	217.0 (98.0)	182.0 (83.0)
8577	8475	12 x 12 (3.7 x 3.7)	359 (1,359)	82.0 (37.0)	63.0 (29.0)
8578	8462	12 x 16 (3.7 x 4.9)	478 (1,809)	97.0 (44.0)	74.0 (33.5)
8579	8476	12 x 20 (3.7 x 6.1)	598 (2,264)	116.0 (53.0)	88.0 (40.0)
8580	8477	12 x 30 (3.7 x 9.1)	897 (3,396)	159.0 (72.0)	120.0 (54.0)
8581	8463	12 x 35 (3.7 x 10.7)	1,047 (3,963)	184.0 (84.0)	138.0 (62.5)
8582	8478	12 x 40 (3.7 x 12.2)	1,196 (4,527)	203.0 (92.0)	152.0 (69.0)
8583	8464	12 x 50 (3.7 x 15.2)	1,496 (5,663)	249.0 (113.0)	187.0 (85.0)
8584	8479	12 x 60 (3.7 x 18.3)	1,795 (6,795)	293.0 (133.0)	219.0 (99.0)
8585	8480	12 x 72 (3.7 x 22.0)	2,154 (8,154)	348.0 (158.0)	260.0 (118.0)
8586	8481	15 x 15 (4.6 x 4.6)	561 (2,124)	104.0 (47.0)	86.0 (39.0)
8587	8482	15 x 20 (4.6 x 6.1)	748 (2,832)	132.0 (60.0)	109.0 (49.0)
8588	8483	15 x 30 (4.6 x 9.1)	1,122 (4,247)	182.0 (83.0)	148.0 (67.0)
8589	8484	15 x 40 (4.6 x 12.2)	1,496 (5,663)	232.0 (105.0)	189.0 (86.0)
8590	8485	15 x 50 (4.6 x 15.2)	1,870 (7,079)	281.0 (128.0)	230.0 (104.0)
8591	8486	15 x 66 (4.6 x 20.1)	2,468 (28,031)	362.0 (164.0)	295.0 (134.0)
8592	8487	15 x 72 (4.6 x 21.9)	2,692 (10,190)	393.0 (178.0)	320.0 (145.0)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Rapid Rise Models

Sidewalls remain down during normal operations, loading and unloading. Vehicles and equipment can drive in and out from any angle. In the case of a spill, the foam ring around the top perimeter of the Containment Berm rises with the level of spilled liquid.



8437



8431

Empty Berm



Filled Berm

Copolymer 2000™ Part#	PVC 22 oz. Part #	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Copolymer 2000 Weight lbs. (kg)	PVC 22 oz. Weight lbs. (kg)
8430	8654	4 x 6 (1.2 x 1.8)	179 (678)	31.0 (14.0)	24.0 (11.0)
8431	8630	6 x 6 (1.8 x 1.8)	269 (1,018)	37.0 (17.0)	30.0 (14.0)
8432	8631	10 x 10 (3.0 x 3.0)	748 (2,831)	69.0 (31.0)	54.0 (24.5)
8710	8655	12 x 12 (3.7 x 3.7)	1,077 (4,077)	85.0 (39.0)	66.0 (30.0)
8437	8656	12 x 26 (3.7 x 7.9)	2,333 (8,831)	151.0 (68.5)	118.0 (54.0)
8711	8632	12 x 30 (3.7 x 9.1)	2,692 (10,190)	171.0 (78.0)	134.0 (61.0)
8712	8657	12 x 40 (3.7 x 12.2)	3,590 (13,590)	218.0 (99.0)	170.0 (77.0)
8713	8633	12 x 50 (3.7 x 15.2)	4,488 (16,989)	266.0 (121.0)	207.0 (94.0)
8714	8658	12 x 60 (3.7 x 18.3)	5,385 (20,384)	313.0 (142.0)	244.0 (111.0)
8715	8659	12 x 72 (3.7 x 22.0)	6,462 (24,461)	370.0 (168.0)	288.0 (131.0)
8716	8660	15 x 15 (4.6 x 4.6)	1,683 (6,371)	115.0 (52.0)	93.0 (42.0)
8717	8661	15 x 20 (4.6 x 6.1)	2,244 (8,495)	141.0 (64.0)	114.0 (52.0)
8718	8662	15 x 30 (4.6 x 9.1)	3,366 (12,742)	195.0 (89.0)	158.0 (72.0)
8719	8663	15 x 40 (4.6 x 12.2)	4,488 (16,989)	248.0 (113.0)	201.0 (91.0)
8433	8664	15 x 50 (4.6 x 15.2)	5,610 (21,234)	302.0 (137.0)	244.0 (111.0)
8720	8665	15 x 60 (4.6 x 18.3)	6,732 (25,483)	356.0 (162.0)	286.0 (130.0)
8434	8666	15 x 66 (4.6 x 20.1)	7,405 (28,028)	388.0 (175.0)	313.0 (142.0)
8721	8667	15 x 72 (4.6 x 21.9)	8,078 (30,579)	420.0 (191.0)	338.0 (153.0)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Wall®

Modular, hard-walled system provides long-term, high-capacity spill containment



Wall sections stack for easy storage and more economical shipping.



Part#	Wall Height & Description	Dimensions in. (mm)	Weight lbs. (kg)
8760	1 ft. (0.3 m) - Straight Section	120 x 12 x 12 (3,048 x 305 x 305)	33.0 (15.0)
8761	1 ft. (0.3 m) - Corner Section	22 x 22 x 12 (559 x 559 x 305)	9.0 (4.0)
8762	2 ft. (0.6 m) - Straight Section	100 x 24 x 24 (2,540 x 610 x 610)	70.0 (32.0)
8763	2 ft. (0.6 m) - Corner Section	35 x 30 x 24 (889 x 762 x 610)	26.0 (12.0)
8764	3 ft. (0.9 m) - Straight Section	72 x 24 x 36 (1,829 x 610 x 914)	60.0 (27.5)
8765	3 ft. (0.9 m) - Corner Section	30 x 30 x 36 (762 x 762 x 914)	36.0 (16.5)
8770	30 ml Textured Polyethylene Liner	Custom (per sq. ft./m)	20 oz/sq yd (0.57 kg/sq yd)

Complete Systems:

Part#	Wall Height	Usable Dimensions ft. (m)	Item Quantity	Containment Cap. gal. (L)	Weight lbs. (kg)
8790	1 ft. (0.3 m)	10 x 49 x 1 (3.0 x 14.9 x 0.3)	12-Straight, 4-Corners, 1-Liner (16x55)	3,978 (15,058)	754 (342.0)
8791	1 ft. (0.3 m)	68 x 68 x 1 (20.7 x 20.7 x 0.3)	28-Straight, 4-Corners, 1-Liner (74x74)	34,802 (131,740)	2,066 (937.1)
8792	2 ft. (0.6 m)	16 x 55 x 2 (4.9 x 16.8 x 0.6)	18-Straight, 4-Corners, 1-Liner (27x66)	13,716 (51,921)	1,821 (826.0)
8793	2 ft. (0.6 m)	63 x 63 x 2 (19.2 x 19.2 x 0.6)	32-Straight, 4-Corners, 1-Liner (74x74)	60,089 (227,462)	3,450 (1,564.9)
8794	3 ft. (0.9 m)	11 x 55 x 3 (3.4 x 16.8 x 0.9)	24-Straight, 4-Corners, 1-Liner (27x71)	14,336 (54,268)	2,157 (978.4)
8795	3 ft. (0.9 m)	61 x 61 x 3 (18.6 x 18.6 x 0.9)	44-Straight, 4-Corners, 1-Liner (77x77)	83,582 (316,392)	3,958 (1,795.3)

Ultra-Containment Berm® Economy Models

Economical design offers cost savings and secure containment. L-shaped aluminum brackets provide sturdy sidewall support.



8251

Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8250	4 x 6 (1.2 x 1.8)	179 (678)	21.0 (9.5)
8251	6 x 6 (1.8 x 1.8)	269 (1,018)	26.0 (12.0)
8252	10 x 10 (3 x 3)	748 (2,831)	52.0 (23.5)
8253	12 x 60 (3.7 x 18.3)	5,385 (20,384)	268.0 (121.5)
8254	15 x 50 (4.6 x 15.2)	5,610 (21,234)	259.0 (117.5)
8255	15 x 66 (4.6 x 20.1)	7,405 (28,028)	334.0 (151.5)

Options: Ground Tarps, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Ultimate Models

Drive-in/drive-out "living hinge" endwalls teamed up with Collapsible sidewalls offer the Ultimate combination — "Hands Free" convenience and an affordable design!



8506

Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8505	12 x 60 (3.7 x 18.3)	5,385 (20,382)	297.0 (134.5)
8506	15 x 50 (4.6 x 15.2)	5,610 (21,234)	290.0 (131.5)
8507	15 x 66 (4.6 x 20.1)	7,405 (28,028)	369.0 (167.0)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Collapsible Wall Models

The Collapsible Wall Model Containment Berm features rugged PVC sidewall assemblies for sidewall support. Simply swivel the "feet" of the PVC supports to lower or raise the sidewalls in just seconds!



8556

Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8405	4 x 6 (1.2 x 1.8)	179 (678)	26.0 (12.0)
8403	6 x 6 (1.8 x 1.8)	269 (1,018)	32.0 (14.5)
8400	10 x 10 (3.0 x 3.0)	748 (2,831)	58.0 (26.5)
8550	10 x 20 (3.0 x 6.1)	1,496 (5,663)	96.0 (44.0)
8551	10 x 30 (3.0 x 9.1)	2,244 (8,495)	132.0 (60.0)
8552	10 x 40 (3.0 x 12.2)	2,992 (11,326)	170.0 (77.0)
8553	10 x 50 (3.0 x 15.2)	3,740 (14,157)	209.0 (95.0)
8554	12 x 12 (3.7 x 3.7)	1,077 (4,077)	69.0 (31.0)
8555	12 x 20 (3.7 x 6.1)	1,795 (6,795)	103.0 (47.0)
8556	12 x 30 (3.7 x 9.1)	2,692 (10,190)	142.0 (64.0)
8557	12 x 40 (3.7 x 12.2)	3,590 (13,590)	183.0 (83.0)
8558	12 x 50 (3.7 x 15.2)	4,488 (16,989)	224.0 (102.0)
8404	12 x 60 (3.7 x 18.3)	5,385 (20,382)	265.0 (120.0)
8559	15 x 15 (4.6 x 4.6)	1,683 (6,371)	95.0 (43.0)
8560	15 x 20 (4.6 x 6.1)	2,244 (8,495)	119.0 (54.0)
8561	15 x 30 (4.6 x 9.1)	3,366 (12,742)	164.0 (74.0)
8562	15 x 40 (4.6 x 12.2)	4,488 (16,989)	210.0 (95.0)
8401	15 x 50 (4.6 x 15.2)	5,610 (21,234)	257.0 (116.5)
8402	15 x 66 (4.6 x 20.1)	7,405 (28,028)	332.0 (150.5)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Compact Models

Compact design folds into a tight package – minimal space required to store onboard trucks and hazmat response vehicles. Sidewalls lower quickly to allow drive in/drive out.

Once sidewalls are lowered, vehicles and heavy equipment can drive in or out.



Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8609	4 x 6 (1.2 x 1.8)	179 (678)	41.0 (18.5)
8610	6 x 6 (1.8 x 1.8)	269 (1,018)	49.0 (22.0)
8611	10 x 10 (3.0 x 3.0)	748 (2,831)	90.0 (41.0)
8680	10 x 20 (3.0 x 6.1)	1,496 (5,663)	146.0 (66.0)
8681	10 x 30 (3.0 x 9.1)	2,244 (8,495)	201.0 (91.0)
8682	10 x 40 (3.0 x 12.2)	2,992 (11,326)	257.0 (117.0)
8683	10 x 50 (3.0 x 15.2)	3,740 (14,157)	312.0 (142.0)
8684	12 x 12 (3.7 x 3.7)	1,077 (4,077)	111.0 (50.0)
8685	12 x 20 (3.7 x 6.1)	1,795 (6,795)	158.0 (72.0)
8686	12 x 30 (3.7 x 9.1)	2,692 (10,190)	216.0 (98.0)
8687	12 x 40 (3.7 x 12.2)	3,590 (13,590)	274.0 (124.0)
8688	12 x 50 (3.7 x 15.2)	4,488 (16,989)	333.0 (151.0)
8612	12 x 60 (3.7 x 18.3)	5,385 (20,384)	391.0 (177.0)
8689	15 x 15 (4.6 x 4.6)	1,683 (6,371)	147.0 (67.0)
8690	15 x 20 (4.6 x 6.1)	2,244 (8,495)	179.0 (81.0)
8691	15 x 30 (4.6 x 9.1)	3,366 (12,742)	243.0 (110.0)
8692	15 x 40 (4.6 x 12.2)	4,488 (16,989)	306.0 (139.0)
8613	15 x 50 (4.6 x 15.2)	5,610 (21,234)	370.0 (168.0)
8614	15 x 66 (4.6 x 20.1)	7,405 (28,028)	472.0 (214.0)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Wellhead Berm®

Captures, collects and contains drips and spills that come from wellheads. Engineered to provide complete (360°) protection.



NEW PRODUCT

Part#	Desc.	Material	Wall Height in. (mm)	Outside Dimensions ft. (m)	Inner Opening Inside Dims. in. (mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8856	Wellhead Berm	Copolymer 2000™	4 (102)	10.5 x 10.5 (3.2 x 3.2)	24 x 24 (610 x 610)	217 (821)	51.0 (23.0)
8858	Wellhead Berm w/ Hood	Copolymer 2000™ & 22oz. PVC (Hood)	4 (102)	10.5 x 10.5 (3.2 x 3.2)	24 x 24 (610 x 610)	217 (821)	63.0 (28.5)

Ultra-Containment Berm® Mini Foam Wall Models

Foldable mini berms (duck ponds) are compact and easy to store but deploy in a moment's notice to respond to a spill. Berms fold down and can be secured using attached strap – provides simple and convenient transport and storage.



Part#	Material of Construction	Dimensions ft. (m) Wall Height: 6 in. (152 mm) Wall Thickness: 2 in. (51 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8850	18 oz. PVC	2 x 2 (0.6 x 0.6)	15 (57)	3 (1.5)
8852	18 oz. PVC	4 x 4 (1.2 x 1.2)	60 (227)	7 (3.0)
8854	18 oz. PVC	4 x 6 (1.2 x 1.8)	75 (284)	9 (4.0)

Ultra-Containment Berm® Modular Models (Gorilla Berm)

Modular construction allows containment areas of any size to be configured. Triangular-shaped, polymer-coated foam support blocks (72”L x 16”W x 6”H) are used with rebar (not included) to provide sidewall structure. Molded-in slots in top of foam blocks hold rebar - secures material in place. Standard material is 38 mil slip resistant PVC.



Modular side walls are easily placed into any configuration during setup.

Part#	Dimensions ft. (m) Wall Height: 6 in. (152 mm)	Number of Modular Walls	Containment Capacity gal. (L)	Weight lbs. (kg)
8740	7 x 13 (2.1 x 4.0)	6	366 (1,385)	165.0 (74.5)
8741	13 x 13 (4.0 x 4.0)	8	665 (2,517)	220.0 (100.0)
8742	13 x 25 (4.0 x 7.6)	12	1,263 (4,781)	332.0 (150.5)
8743	13 x 31 (4.0 x 9.4)	14	1,563 (5,917)	387.0 (176.0)
8744	13 x 34 (4.0 x 13.1)	18	2,161 (8,180)	491.0 (222.5)
8745	13 x 55 (4.0 x 16.8)	22	2,759 (10,444)	610.0 (278.0)
8746	13 x 61 (4.0 x 18.6)	24	3,059 (11,580)	666.0 (302.0)
8747	25 x 55 (7.6 x 16.8)	26	5,243 (19,847)	868.0 (393.5)
8748	31 x 55 (9.4 x 16.8)	28	6,485 (24,548)	1,004.0 (455.5)
8749	55 x 55 (16.8 x 16.8)	36	11,452 (43,351)	1,502.0 (681.5)

Rebar not included - 1" diameter recommended



11542 Davis Creek Court, Jacksonville, Florida 32256 USA
(800) 353-1611 · 1-904-292-1611 · 1-904-292-1325 fax
spillcontainment.com · info@spillcontainment.com



All Ultra-Containment Berms meet SPCC and EPA 40 CFR 264.175 spill containment regulations. Custom materials and sizes available.