



ULTRATECH
INTERNATIONAL, INC.

Ultra-Drain Guard, Economy Frame Model Specification

Product: Ultra-Drain Guard, Economy Frame Model

Manufacturer:

UltraTech International, Inc.
11542 Davis Creek Court
Jacksonville, FL 32256 USA

Email: info@stormwaterproducts.com
www.stormwaterproducts.com



1.0 Description of Work

1.1 This work shall consist of furnishing, installing, maintaining, and removing Ultra-Drain Guard, Economy Frame Model sediment control device as directed by the engineer or as shown on the site drawings.

2.0 Ultra-Drain Guard, Economy Frame Model Materials

2.1 There two types of Ultra-Drain Guard, Economy Frame Model

Ultra-Drain Guard, Economy Frame Model (Standard) - Overflow optional

Ultra-Drain Guard, Economy Frame Model (Round) - Overflow included

2.2 Ultra-Drain Guard, Economy Frame Model shall be manufactured from a specially designed nonwoven polypropylene geotextile and sewn by a double needle machine, using a high strength nylon thread.

2.3 Ultra-Drain Guard, Economy Frame Model shall be manufactured to fit the opening of the catch basin or drop inlet. Ultra-Drain Guard, Economy Frame Model will have the following features: included frame that adjusts to fit the catch basin opening.

2.4 The Ultra-Drain Guard, Economy Frame Model unit shall utilize a nonwoven fabric with the following characteristics:

Specifications for Ultra-Drain Guard, Economy Frame Model

Property	Test Method	Units	Test Results
Grab Tensile	ASTM D4632	lbs	285 x 293
Grab Elongation	ASTM D4632	%	78 / 72
Puncture	ASTM D6241	lbs	525
Trapezoid Tear	ASTM D4533	lbs	85 x 85
AOS	ASTM D4751	US Sieve	80
Flow Rate	ASTM D4491	gal/min/ft ²	90
Permittivity	ASTM D4491	sec ⁻¹	1.4

3.0 Construction Sequence

- 3.1 To install Ultra-Drain Guard, Economy Frame Model in the catch basin, remove grating. Remove any excess dirt or debris and place the unit on ledge that supports the grating. If necessary, adjust frame to fit.
- 3.2 To remove Ultra-Drain Guard, Economy Frame Model, remove grating from catch basin. Remove unit from catch basin and empty if necessary or discard as per local requirements.
- 3.3 Ultra-Drain Guard, Economy Frame Model is reusable if not saturated with hydrocarbons. Once the construction cycle is complete, remove Drain Guard from the catch basin and clean. Ultra-Drain Guard, Economy Frame Model should be stored out of sunlight until the next use.

4.0 Basis of Payment

- 4.1 Payment for all Ultra-Drain Guard, Economy Frame Model units used during construction is to be included in the bid price for the overall erosion and sediment control plan unless unit price is requested.

Note: This information is provided as reference only and is not intended as a warranty or guarantee. UltraTech International, Inc. assumes no liability in connection with the use of this information (8/19/24).