



Ultra-Drain Seal® Clear Model Product Data Sheet

Description: A non-absorbing urethane pad that forms a temporary bond with drains to stop leaks from entering the drain.

Item#	Description	Length in (mm)	Width in (mm)	Height in (mm)	Weight lb. (kg)
2200	Clear. Square.	18.0 (458)	18.0 (458)	.375 (9.5)	5.0 (2.5)
2201	Clear. Square.	24.0 (610)	24.0 (610)	.375 (9.5)	8.0 (3.5)
2202	Clear. Square.	36.0 (915)	36.0 (915)	.375 (9.5)	20.0 (9.0)
2203	Clear. Square.	42.0 (1,067)	42.0 (1,067)	.375 (9.5)	23.0 (10.5)
2204	Clear. Square.	48.0 (1,220)	48.0 (1,220)	.375 (9.5)	36.0 (17.0)
2205	Clear. Square.	54.0 (1,372)	54.0 (1,372)	.375 (9.5)	41.0 (18.5)
2208	Clear. Circular.		12.0 Dia. (305)	.375 (9.5)	3.0 (1.5)
2209	Clear. Circular.		20.0 Dia. (508)	.375 (9.5)	6.0 (3.0)
2210	Clear. Circular.		30.0 Dia. (762)	.375 (9.5)	11.0 (5.0)
2211	Clear. Circular.		42.0 Dia. (1,067)	.375 (9.5)	19.0 (9.0)
2206	Clear. Rectangular.	18.0 (458)	58.0 (1,474)	.375 (9.5)	16.0 (7.0)
2207	Clear. Rectangular.	36.0 (915)	58.0 (1,474)	.375 (9.5)	26.0 (12.0)

Application: For use in response to machine leaks and small chemical spills. They can be quickly deployed to seal floor or storm drains until the spill or leak can be cleaned in accordance with local and state regulations.

Product Features:

- + Clear material provides unobstructed view of covered drains – enables responders to make sure a complete seal is made.
- + No more guess work about Drain Seal effectiveness – quickly see if spills are entering the drain through cracks in the surface, imperfections in the grating, or other irregularities that can break the seal.
- + Reinforcing mesh is sandwiched between layers of polyurethane – increases durability and resistance to tearing.
- + Unique, urethane construction allows the pad to deform and seal off most drains – temporarily seals to any smooth surface.
- + Helps comply with SPCC and NPDES.

Composition: 100% polyurethane.

Material Specifications:

Specification	Value	
Style	Pad (Square/ Circular/ Rectangular)	
Color	Clear	
Intended for	Storm and Floor Drains	
Max liquid temp exposure	225°F for up to 30 minutes	107.2°C for up to 30 minutes
Storage temp range	0°- 120°F	-17.7° - 48.8°C
Temperature limit	0°- 160°F	-17.7° - 71.1°C
Sold as	1 each	
Composition	Polyurethane	