



ULTRATECH
INTERNATIONAL, INC.

Ultra-Drain Seal®

Product Data Sheet

Description: A non-absorbing urethane pad that forms a temporary bond with drains to stop leaks from entering the drain.

Item#	Description	Length in (mm)	Width in (mm)	Height in (mm)	Weight Lb. (kg)
2126	Safety orange. Square.	18.0 (458)	18.0 (458)	.375 (9.5)	5.0 (2.5)
2127	Safety orange. Square.	24.0 (610)	24.0 (610)	.375 (9.5)	8.0 (3.5)
2130	Safety orange. Square.	36.0 (915)	36.0 (915)	.375 (9.5)	20.0 (9.0)
2131	Safety orange. Square.	42.0 (1,067)	42.0 (1,067)	.375 (9.5)	23.0 (10.5)
2132	Safety orange. Square.	48.0 (1,220)	48.0 (1,220)	.375 (9.5)	36.0 (17.0)
2133	Safety orange. Square.	54.0 (1,372)	54.0 (1,372)	.375 (9.5)	41.0 (18.5)
2134	Safety orange. Circular.	12.0 Dia. (305)		.375 (9.5)	3.0 (1.5)
2135	Safety orange. Circular.	20.0 Dia. (508)		.375 (9.5)	6.0 (3.0)
2136	Safety orange. Circular.	30.0 Dia. (762)		.375 (9.5)	11.0 (5.0)
2137	Safety orange. Circular.	42.0 Dia. (1,067)		.375 (9.5)	19.0 (9.0)
2124	Safety orange. Rectangular.	18.0 (458)	58.0 (1,474)	.375 (9.5)	16.0 (7.0)
2125	Safety orange. Rectangular.	36.0 (915)	58.0 (1,474)	.375 (9.5)	26.0 (12.0)

Application: For use in response to machine leaks and small chemical spills. They can be quickly deployed to seal floor or storm drains until the spill or leak can be cleaned in accordance with local and state regulations.

Product Features:

- + The Ultra- Drain Seal is an essential part of your spill response kit that can be quickly deployed to seal drains and prevent spills or leaks from going down the drain.
- + Reinforced mesh is sandwiched between layers of polyurethane – increases durability and resistance to tearing.
- + Unique, urethane construction allows the pad to deform and seal off most drains – temporarily seals to any smooth surface.
- + A valuable addition to any emergency response plan, spill kit, or stormwater management program.
- + Unlike some alternative products, BOTH sides will quickly seal drains – there is no specified top or bottom.
- + Flexible non-absorbing material with reinforced, tear resistant mesh.
- + Resists oil, water and most aggressive chemicals, cleans with soap and water.
- + NOT intended for long term outdoor use (more than 2 hours), as UV exposure and/or heat for extended periods of time can degrade the product.

Composition: 100% polyurethane.

Material Specifications:

Specification	Value	
Style	Pad (Square/ Circular/ Rectangular)	
Color	Safety Orange	
Intended for	Storm and Floor Drains	
Max liquid temp exposure	225°F for up to 30 minutes	107.2°C for up to 30 minutes
Storage temp range	0°- 120°F	-17.7° - 48.8°C
Temperature limit	0°- 160°F	-17.7° - 71.1°C
Sold as	1 each	
Composition	Polyurethane	