

## Ultra-HydroKleen® Data Sheet

| Ultra-HydroKleen Unit Specifications |   |
|--------------------------------------|---|
| Property                             | Value   |
| Sediment Capacity                    | 0.7 ft³ (equivalent of 70 – 80 lbs of sediment) |
| Treated Effluent Flow Rate           | 30 – 35 gpm                                     |
| Flow Rate with Overflow              | 135 ft <sup>3</sup> /min (1,000 gpm)            |
| Sampling Option Available            | Yes   |
| Media Capacity                       | 3 Media Filters                                 |

| Media Filter Specifications |   |
|-----------------------------|---|
| Media Type                  | Capacity Information  |
| Heavy Metal Removal Media   | • Each media filter can remove up to 285 grams of heavy metals  |
|                             | Removal rates up to 50% per filter bag  |
|                             | See Heavy Metal Removal Data Sheet for more information   |
|                             | <ul> <li>Dry Media Filter Weight is approximately 8.5 lbs</li> </ul>  |
| PhosFilter                  | • Each media filter can remove up to 6.6 lbs of phosphorus with up to 95% efficiency  |
|                             | Dry Media Filter Weight is approximately 12.5 lbs   |
| Sorb 44                     | • Each media filter can absorb up to 1.33 gallons (5 liters) of hydrocarbon   |
|                             | <ul> <li>Dry Media Filter Weight is approximately 2.0 lbs</li> </ul>  |
| Activated Carbon            | <ul> <li>Each media filter is filled with granular activated carbon. This is primarily used as a polishing filter, due to its immense surface area and the wide range of components it is capable of absorbing. Helps with removing odors.</li> </ul> |
|                             | <ul> <li>Dry Media Filter Weight is approximately 9.0 lbs</li> </ul>  |

Updated: 07.18.25