

## **Product Data Sheet**

## Ultra-Berm Builder

## Build a barrier around machinery or equipment that is permanently mounted or cannot easily be moved

- + Component system provides flexibility to create a semi-permanent, high-visibility custom barrier.
- + Durable, vinyl covering resists oils, coolants and most chemicals.
- + Cut to length and secure to floor with included sealant, then seal seams with the vinyl adhesive.
- + Economical containment for leaks and spills around machinery and equipment - no need to build expensive cement or angle iron curbs.
- + High-visibility yellow color draws attention to barrier for increased safety.
- + Easy removal requires only a flat-bladed shovel.



Part#	Description	Dimensions in. (mm)	Qty	Weight lbs. (kg)
2" Model				
8640	Full Kit	50' x 5.5" x 2" (15.2 m x 140 mm x 51 mm)	1/box	21.0 (9.5)
8641	Straight Section	15' x 5.5" x 2" (4.6 m x 140 mm x 51 mm)	1/box	6.0 (3.0)
8642	Corner	7.3" x 5.5" x 2" (184 mm x 140 mm x 51 mm)	2/box	2.0 (1.0)
8643	Connecting Collar	10' x 4" (3m x 102mm)	1/box	1.0 (0.5)
4" Model				
8674	Straight Section	60 x 7.3 x 4 (1,524 x 184.15 x 101.6)	2/box	60 (27.2)
8675	Corner	9.5 x 7.3 x 4 (241.3 x 184.15 x 101.6)	2/box	3.0 (1.4)
8676	Wall End	10 x 7.3 x 4 (254 x 184.15 x 101.6)	2/box	2 (0.9)
6" Model				
8677	Straight Section	60 x 9 x 6 (1524 x 228.6 x 152.4)	2/box	9 (4.08)
8678	Corner	10.5 x 9 x 6 (266.7 x 228.6 x 152.4)	2/box	3.0 (1.4)
8679	Wall End	11 x 9 x 6 (279.4 x 228.6 x 152.4)	2/box	2 (0.9)
Options				
8644	Floor Sealant (10.3 fl. oz. tube)	N/A	6/box	8.0 (3.5)
8645	Vinyl Adhesive (8 oz. can)	N/A	1/box	1.0 (0.5)

Continued on the next page



## Specifications

Color	Yellow		
Barrier Type	Vinyl berm		
Install/Deploy Type	Glued In Place Barrier		
Intended Use	For Smooth Surfaces; Walk-On		
Max liquid temp exposure	Max Exposure Limit 225°F for up to 30 Minutes		
Storage Temp Range	Store Between 0°F and 120°F		
Temperature Limit	Works from -22°F to 160°F		
# per Pallet	5		
Composition	Cover, Seam Mender - 18 oz. Vinyl-Coated Fabric Core -Polyurethane Foam Sealant - Sili-Thane™ 803 Sealant		
Shelf life	365 days		