



**ULTRATECH**  
INTERNATIONAL, INC

## Ultra-Sidewinder, Large Specifications

Part#	1840, 1841, 1842, 1843
Dimensions In. (mm)	System: 34 x 13 <sup>5</sup> / <sub>8</sub> x 2 <sup>1</sup> / <sub>8</sub> (863 x 346 x 54) Extension: 14 <sup>1</sup> / <sub>8</sub> x 13 <sup>5</sup> / <sub>8</sub> x 2 <sup>1</sup> / <sub>8</sub> (358 x 346 x 54)
Weight	System with endcaps: 13.5 (6.0) Extension: 4.5 (2.0)
Load Capacity	260 lbs./in <sup>2</sup> (18.3 kg./cm <sup>2</sup> )
Load Capacity per axle:	13,500 lbs. (6,123 kg.)
Construction	Injection-molded acrylonitrile butadiene styrene (ABS) plastic and injection-molded Santoprene™ vulcanized rubber tabs
Internal channel opening	3"W x 1 <sup>1</sup> / <sub>2</sub> "H (76mm x 38mm)
Operating Temp.	-40°F to 120°F (-40°C to 49°C)

- Systems include two (2) end caps. Extensions can be added for increased system length (end caps are not included with extensions). Segments can be removed to create custom lengths.
- Modular design allows for easy reconfiguration or repair, even with the cable or cord in place.
- Unit is designed for office and light-industrial use and is designed to be run on flat, stable surfaces. Not intended to span gaps, holes or trenches with any weight load.
- The system is capable of withstanding loads from vehicles with pneumatic tires but not designed to be run over by any equipment or vehicle with rigid wheels.

