



ULTRATECH
INTERNATIONAL, INC.

Ultra-Containment Berm® Economy Model



Economical L-shaped bracket berm design offers cost savings and secure spill containment

- + L-shaped brackets provide sturdy sidewall support.
- + 12" sidewall contains spills in drilling and fracking locations.
- + No frames, components or excess material outside of sidewalls — excellent for use as spill containment area inside of storage sheds and other buildings or structures where floor space is a premium.
- + Standard material of construction is 30 mil reinforced polyethylene. Other materials available upon request.
- + Meets SPCC and EPA Container Storage Regulations 40 CFR 264.175.



Rugged polyethylene material can withstand a variety of containment needs.

Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8240	6 x 6 (1.9 x 1.9)	269 (1018.28)	9.0 (4.1)
8241	10 x 10 (3.05 x 3.05)	748 (2831.49)	23.0 (10.4)
8242	12 x 12 (3.65 x 3.65)	1077 (4076.88)	29.0 (13.2)
8243	12 x 25 (3.65 x 7.62)	2244 (8494.464)	49.0 (22.2)
8244	10 x 50 (3.65 x 15.24)	3740 (14157.44)	84.0 (38.1)
8245	12 x 50 (3.65 x 15.24)	4488 (1695.86)	88.0 (40.0)
<i>*Other stock sizes and custom sizes available.</i>			