

Top Sellers

Construction Compliance & Stormwater Management



ULTRATECH
INTERNATIONAL, INC.

Hundreds of Other Construction Compliance and Stormwater Management Products.
Visit www.constructioncompliance.com to see more.

Ultra-Drain Guard®



Keep sediment and other pollutants from entering the water system with Ultra-Drain Guard catch basin inserts

- + This simple, yet specifically designed and engineered geotextile fabric catch basin insert can be installed in most drains. The heavy-duty material removes contaminants like litter, sand, and oil from stormwater flow.
- + Installation is quick and easy - Simply raise the grate, place the Ultra-Drain Guard over the opening and carefully lower the grate back into place, pinching the fabric in place to keep the unit secure.
- + Removes hydrocarbons, dirt, sand and other contaminants.
- + Exceeds 80% sediment removal efficiency.
- + Designed for practical use in industrial facilities, construction sites, parking lots, and "drive-up" retail facilities.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.

Ultra-Drain Guards®
Oil & Sediment Plus

Ultra-Drain Guards®
Oil & Sediment Model



Patents: See www.ultratechpatents.com

| Part# | Description | Dimensions in. (mm) | Performance | Weight each lbs. (kg) |
|-------|------------------------------------|------------------------------------|--|-----------------------|
| 9217 | Oil & Sediment (1-Pack) | 48 x 36 x 18 (1,220 x 915 x 458) | Up to .87 gals. (3.5 L) of oil and up to 40 lbs. (18 kg) of sediment | 1.0 (0.5) |
| 9218 | Oil & Sediment (10-Pack) | 48 x 36 x 18 (1,220 x 915 x 458) | Up to .87 gals. (3.5 L) of oil and up to 40 lbs. (18 kg) of sediment | 1.0 (0.5) |
| 9356 | Oil & Sediment Large (1-Pack) | 60 x 60 x 18 (1,524 x 1,524 x 458) | Up to 1.55 gals. (6 L) of oil and up to 40 lbs. (18 kg) of sediment | 2.0 (1.0) |
| 9219 | Oil & Sediment Plus (1-Pack) | 48 x 36 x 18 (1,220 x 915 x 458) | Up to 1.38 gals. (5 L) of oil and up to 40 lbs. (18 kg) of sediment | 2.0 (1.0) |
| 9220 | Oil & Sediment Plus (10-Pack) | 48 x 36 x 18 (1,220 x 915 x 458) | Up to 1.38 gals. (5 L) of oil and up to 40 lbs. (18 kg) of sediment | 2.0 (1.0) |
| 9358 | Oil & Sediment Plus Large (1-Pack) | 60 x 60 x 18 (1,524 x 1,524 x 458) | Up to 2.06 gals. (8 L) of oil and up to 40 lbs. (18 kg) of sediment | 3.0 (1.5) |
| 9227 | Trash & Debris (1-Pack) | 48 x 36 x 18 (1,220 x 915 x 458) | 1 cu. ft. (28 L) before reaching bypass ports | 1.0 (0.5) |
| 9235 | Grate Hook | 26 L x 5 W (handle) x .75 thick | - | 4.0 (2.0) |



Ultra-Drain Guard® Economy Frame Model

A catch basin insert that adjusts to the size of the storm drain

- + Metal frame quickly adjusts to fit most drains - keeps the Ultra-Drain Guard in place, even when grating is removed.
- + Removes up to 0.5 gallons of hydrocarbons as well as dirt, sand, and other contaminants.
- + Adjustable catch basin insert quickly re-sizes to fit almost any storm drain – no trimming of excess fabric required.
- + Quick and clean installation – no measuring or trimming required.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.



| Part# | Min Dimensions/Unit in (mm) | Max Dimensions/Unit in (mm) | Performance/Unit | Weight/Unit lbs. (kg) |
|----------------------|---|-------------------------------------|--|-----------------------|
| 8935 - Square | 16 x 20 x 18 (406 x 508 x 457) | 28 x 36 x 18 (711 x 914 x 457) | Up to 0.5 gallons (1.9 L) of oil and up to 40 lbs. (18 kg) of sediment | 3.0 (1.4) |
| 8920 - Round | 22 x 22 x 14 (558.8 x 558.8 x 355.6) | 25 x 25 x 14 (635 x 635 x 355.6) | Up to 0.5 gallons (1.9 L) of oil and up to 40 lbs. (18 kg) of sediment | 1 (0.45) |

Ultra-Curb Guard Plus®

Protect curb inlets from oil and sediment-laden stormwater runoff

- + Quick and easy installation.
- + Modular design — build to any length.
- + Units can be quickly and easily connected to form longer lengths.
- + Wedge-shaped, heavy-duty foam secures unit in curb inlet.
- + Woven, polypropylene material provides high flow rate — will not cause ponding or flooding.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.



| Part# | Dimensions in. (mm) | Containment Cap. gal. (L) | Weight lbs. (kg) |
|-------------|-----------------------------|---------------------------|------------------|
| 9248 | 4 dia. x 36 L (102 x 915) | 1 (3.79) | 6.0 (3.0) |
| 9251 | 4 dia. x 48 L (102 x 1,220) | 1.4 (5.3) | 8.0 (3.5) |

Ultra-Flood Stopper® NEW PRODUCT

Sandless sandbags protect property against floods, leaks, and other liquid emergencies

- + Easy-to-use and transport - bags and tubes weigh approximately one pound each before being activated with fresh water
- + Quick acting - In minutes, the bag fills to capacity, ready to prevent floods and leakage from causing damage
- + Safe, non-toxic, and can typically be disposed of at local landfill



| Part# | Description | Dimensions - Dry in. (mm) | Weight - Dry lbs. (kg) | Weight - Activated lbs. (kg) |
|-------------|-------------|-------------------------------|------------------------|------------------------------|
| 5340 | 6-Pack | 12 x 24 x .5 (305 x 610 x 13) | Approx. 0.37 lbs (.17) | Approx. 30 lbs. (13.6) |

Ultra-Drain Guard® Heavy Metal Model

Remove heavy metal runoff water at the storm drain

- + Specialized catch basin insert has “quilted” sections sewn into the body of the unit where stormwater flows through.
- + An impermeable PVC skirt at the top of the unit funnels all water to the lower portion of the Ultra-Drain Guard where it is forced to move through the media before it can move on into the storm drain.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) when used as Best Management Practice in Storm Water Pollution Prevention Plans.



Patents: See www.ultratechpatents.com

| Part# | Dimensions in (mm) | Flow Rate GPM (LPM) | Sediment Cap. lbs. (kg) | Oil Cap. lbs. (kg) | Metal Cap. grams | Weight lbs. (kg) |
|-------------|-------------------------------------|---------------------|-------------------------|--------------------|------------------|------------------|
| 9397 | 48 x 36 x 18 (1,219 x 914 x 457) | 275 (1,040) | 30 (13.5) | 0.23 (0.87) | 190 | 8.0 (3.5) |

Ultra-Dewatering Bag®

Contain sediment and oil pumped out during dewatering operations

- + Retains both oil and sediment, offering a combination of benefits not available in alternative dewatering bags.
- + Accommodates up to 4” discharge hose.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) when used as Best Management Practice in Stormwater Pollution Prevention Plans.



| Part# | Capacity cu. ft. (L) | Dimensions ft. (mm) | Weight lbs. (kg) |
|----------------|----------------------|-------------------------|------------------|
| 9729-0S | 6 (170) | 3 x 4 (915 x 1,220) | 2.0 (1.0) |
| 9724-0S | 18 (510) | 6 x 6 (1,829 x 1,829) | 5.0 (2.5) |
| 9723-0S | 32 (906) | 8 x 8 (2.4 x 2.4) | 5.0 (2.3) |
| 9725-0S | 150 (4,247) | 10 x 15 (3,048 x 4,572) | 21.0 (9.5) |
| 9727-0S | 225 (6,371) | 15 x 15 (4,572 x 4,572) | 30.0 (14.0) |

Other sizes available.

Ultra-Filter Sock® MADE IN USA

Stop harmful substances from entering the stormwater system

- + Use in front of storm drains, around downspouts, in gullies, and ditches.
- + Woven polymer casing allows water to pass through quickly while filtration media inside removes pollutants.
- + Available in 9-foot lengths. Units can be overlapped for longer coverage.
- + Available with different types of media depending on which pollutant is present.



| Part# | Description | Dimensions in. (mm) | Removes | Weight lbs. (kg) |
|-------------|---------------------|---------------------------------|-----------------|------------------|
| 9453 | Activated Carbon | 108 x 7 x 4 (2,743 x 178 x 102) | Chemical & Odor | 40.0 (18.0) |
| 9455 | Sorb 44 | 108 x 7 x 4 (2,743 x 178 x 102) | Hydrocarbons | 15.0 (7.0) |
| 9457 | Sediment Removal | 108 x 7 x 4 (2,743 x 178 x 102) | Sediment | 40.0 (18.0) |
| 9456 | Phos Filter | 108 x 7 x 4 (2,743 x 178 x 102) | Phosphorous | 66.0 (30.0) |
| 9454 | Heavy Metal Removal | 108 x 7 x 4 (2,743 x 178 x 102) | Heavy Metals | 35.0 (16.0) |



Ultra-Inlet Guard® Plus Model




Protect drains and inlets without lifting any grates

- + Keeps dirt, sand, sediment, trash, and debris out of drains.
- + Quick and easy installation using built-in magnets — no more lifting heavy catch basin grates.
- + Heavy-duty material (non-woven, polypropylene geotextile) allows up to 92 gal/ft²/min. through drains.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.



9164



Built in magnets

Patents: See www.ultratechpatents.com

| Part# | Dimensions in. (mm) | Oil & Sediment | Curb Style | Weight lbs. (kg) |
|-------|-----------------------|----------------|------------|------------------|
| 9160 | 24 x 24 (610 x 610) | ● | | 5.0 (2.5) |
| 9161 | 24 x 36 (610 x 915) | ● | | 5.0 (2.5) |
| 9162 | 24 x 48 (610 x 1,220) | ● | | 5.0 (2.5) |
| 9163 | 24 x 24 (610 x 610) | ● | ● | 5.0 (2.5) |
| 9164 | 24 x 36 (610 x 915) | ● | ● | 5.0 (2.5) |
| 9165 | 24 x 48 (610 x 1,220) | ● | ● | 6.0 (3.0) |

Ultra-Containment Sumps®



Rigid secondary containment for fuel tanks

- + Spill solution - Eliminate costly spills while storing fuels, oils and other hazardous liquids.
- + Rugged, all-polyethylene construction will not rust or corrode.
- + Pullover Cover option keeps rainwater out, yet allows easy access for pumping waste collection.
- + Meets Stormwater, SPCC, and EPA Container Storage Regulation 40 CFR 264.175.



| Part# | Description | Top Outside Dims x H in. (mm) | Inside Bottom Dimensions in. (mm) | Containment Cap. gal. (L) | Weight lbs. (kg) |
|-------|--------------------------------------|--------------------------------------|-----------------------------------|---------------------------|------------------|
| 2800 | 275 Sump Without Drain | 85 x 44 x 29 (2,159 x 1,118 x 737) | 71 x 31 (1,803 x 788) | 360 (1,363) | 82.0 (37.0) |
| 2801 | 275 Sump With 3/4" Drain | 85 x 44 x 29 (2,159 x 1,118 x 737) | 71 x 31 (1,803 x 788) | 360 (1,363) | 82.0 (37.0) |
| 2823 | 550 Sump Without Drain | 90 x 61 x 32.8 (2,286 x 1,549 x 832) | 75 x 47.8 (1,905 x 1,213) | 605 (2,291) | 108.0 (49.0) |
| 2820 | 550 Sump With 3/4" Drain | 90 x 61 x 32.8 (2,286 x 1,549 x 832) | 75 x 47.8 (1,905 x 1,213) | 605 (2,291) | 108.0 (49.0) |
| 2830 | 1000 Sump Without Drain | 149 x 64 x 33 (3,785 x 1,626 x 838) | 138 x 52 (3,505 x 1,321) | 1,100 (4,164) | 244.0 (111.0) |
| 2831 | 1000 Sump With 3/4" Drain | 149 x 64 x 33 (3,785 x 1,626 x 838) | 138 x 52 (3,505 x 1,321) | 1,100 (4,164) | 244.0 (111.0) |
| 2832 | 1000 Sump With 2" Drain | 149 x 64 x 33 (3,785 x 1,626 x 838) | 138 x 52 (3,505 x 1,321) | 1,100 (4,164) | 244.0 (111.0) |
| 2810 | Optional Pullover Cover for 275 Sump | | | | |

Ultra-Drain Guard® Reusable Model

Capture dirt and sediment at construction sites and other "high erosion" areas

- + Rugged polypropylene construction can be easily rinsed and reused.
- + Deep accumulation pocket (36") can hold up to 500 lbs. of soil, sand, sediment, and dirt.
- + Designed for easy removal with backhoe, forklift, or other equipment.
- + Custom sizes available.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.



| Part# | Dimensions in. (mm) | Weight lbs. (kg) |
|-------|----------------------------------|------------------|
| 9332 | 24 x 24 x 36 (610 x 610 x 914) | 3 (1.4) |
| 9330 | 36 x 24 x 36 (914 x 610 x 914) | 3 (1.4) |
| 9331 | 48 x 24 x 36 (1,219 x 610 x 914) | 3 (1.4) |

Ultra-Pipe Sock®



Control the flow of sediment and oil out of headwall and other types of pipes



- + Also use in pond applications where vertical pipes extend above the water surface, and preventing sediment in-flow during high-water events is required.
- + Several standard and custom sizes available.
- + Helps comply with NPDES, 40 CFR 122.26 (1999).



9705-OS

| Part# | Dimensions in. (mm) | Oil Capacity gal. (L) | Weight lbs. (kg) |
|---------|------------------------------|-----------------------|------------------|
| 9705-OS | 8 dia. x 60 L (204 x 1,524) | 1.7 (6.4) | 2.0 (1.0) |
| 9706-OS | 12 dia. x 60 L (305 x 1,524) | 2.6 (9.8) | 3.0 (1.5) |
| 9707-OS | 16 dia. x 60 L (407 x 1,524) | 3.5 (13.2) | 3.0 (1.5) |

Ultra-Grate Guards®

Capture sediment, silt, and other debris before it enters our waterways

- + For use with flat grate catch basins.
- + Allows run-off to flow through while blocking sediment and/or capturing oil.
- + Standard and custom sizes available.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.



Patents: See www.ultratechpatents.com

| Part# | Model | Dimensions in. (mm) | Weight lbs. (kg) |
|----------|----------------|---------------------------------|------------------|
| 9273-SED | Sediment Only | 24 x 24 x 4 (610 x 610 x 102) | 2.0 (1.0) |
| 9276-SED | Sediment Only | 24 x 36 x 4 (610 x 914 x 102) | 2.0 (1.0) |
| 9277-SED | Oil & Sediment | 24 x 40 x 4 (610 x 1,016 x 102) | 2.0 (1.0) |
| 9274-SED | Oil & Sediment | 28 x 28 x 4 (711 x 711 x 102) | 2.0 (1.0) |

Other stock sizes and custom sizes available.

Ultra-Concrete Washout Berm® Economy Model

Capture concrete washout in portable and economical berm



- + Heavy-duty, rugged construction can be re-used multiple times (liner must be replaced before each use).
- + Special water & oil coating as well as water-resistant adhesive help provide extended life and reusability.
- + Heavy-duty, 6 mil liner (included) helps contain washout. Quickly and easily replaced.
- + Specially designed slotted edges “lock” liner in place and keeps it secure.
- + Chemically-resistant materials are compatible with concrete washout, paint waste and other construction materials.
- + Helps comply with EPA regulations.



Designed to fold flat for efficient and inexpensive shipping and storage.

| Part# | Dimensions in. (mm) | Capacity gal. (L) | Weight lbs. (kg) |
|-------|------------------------------------|-------------------|------------------|
| 3515 | 30 x 30 x 15 (762 x 762 x 381) | 50 (189) | 5 (2.3) |
| 3516 | 48 x 48 x 15 (1,219 x 1,219 x 381) | 140 (530) | 9 (4) |
| 3517 | 60 x 60 x 12 (1,524 x 1,524 x 305) | 180 (681) | 11 (5) |

Ultra-Hard Top Plus Model®



Store hazardous drums safely outdoors with pumps and funnels in place

- + Tall head space easily accommodates rotary drum pumps and large conical funnels.
- + Low profile containment pallet positions drum-top funnels at a safe, convenient level to pour hazardous wastes.
- + 100% polyethylene construction will not rust or corrode.
- + Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.
- + Helps meet Stormwater Management Regulations — NPDES, 40 CFR 122.26 (1999).



9612



| Part# | Description | Dimensions in. (mm) | Uniformly Dist. Load lbs. (kg) | Contain. Cap. gal. (L) | Weight lbs (kg) |
|-------|-----------------------------|--|--------------------------------|------------------------|-----------------|
| 9640 | P1 Plus (1-Drum) | 36 x 36 x 66 (915 x 915 x 1,677) | 800 (363) | 70 (265) | 75.0 (34.0) |
| 9612 | P2 Plus (2-Drum) | 67.3 x 41.3 x 74 (1,708 x 1,047 x 1,677) | 4,500 (2,041) | 66 (250) | 260.0 (118.0) |
| 9636 | P4 Plus (4-Drum) | 64.5 x 62 x 79 (1,638 x 1,575 x 2,007) | 9,000 (4,082) | 75 (284) | 440.0 (200.0) |
| 0676 | Ramp - Polyethylene & Steel | 55.5 x 28.5 x 8.8 (1,410 x 724 x 222) | 700 (318) | — | 43.0 (19.5) |

Also available with drain

Ultra-Drain Seal®



Stop spills from going down the drain

- + Reinforcing mesh is “sandwiched” between layers of polyurethane — increases durability and resistance to tearing.
- + Unique, urethane construction allows the pad to deform and seal off most drains — temporarily “seals” to any smooth surface.
- + A valuable addition to any emergency response plan, spill kit, SPCC, or stormwater management program.
- + Unlike some alternative products, BOTH sides will quickly seal drains — there is no specified “top” or “bottom.”



Patents: See www.ultratechpatents.com

| Part# | Shape | Dimensions in. (mm) | Weight lbs. (kg) |
|-------|-------------|--|------------------|
| 2126 | Square | 18 x 18 x .4 (457.2 x 457.2 x 9.7) | 5.0 (2.5) |
| 2127 | Square | 24 x 24 x .4 (609.6 x 609.6 x 9.7) | 8.0 (3.5) |
| 2130 | Square | 36 x 36 x .4 (914.4 x 914.4 x 9.7) | 20.0 (9.0) |
| 2131 | Square | 42 x 42 x .4 (1,066.8 x 1,066.8 x 9.7) | 23.0 (10.5) |
| 2132 | Square | 48 x 48 x .4 (1,219.2 x 1,219.2 x 9.7) | 36.0 (17.0) |
| 2133 | Square | 54 x 54 x .4 (1,371.6 x 1,371.6 x 9.7) | 41.0 (18.5) |
| 2134 | Circular | 12 dia. x .4 (304.8 x 304.8 x 9.7) | 3.0 (1.5) |
| 2135 | Circular | 20 dia. x .4 (508 x 508 x 9.7) | 6.0 (3.0) |
| 2136 | Circular | 30 dia. x .4 (762 x 762 x 9.7) | 11.0 (5.0) |
| 2137 | Circular | 42 x 42 x .4 (1,066.8 x 1,066.8 x 9.7) | 19.0 (9.0) |
| 2124 | Rectangular | 58 x 18 x .4 (1,473.2 x 457.2 x 9.7) | 16.0 (7.0) |
| 2125 | Rectangular | 58 x 36 x .4 (1,473.2 x 914.4 x 9.7) | 26.0 (12.0) |

Note: Not intended for long-term outdoor use (more than two [2] hours), as UV exposure and/or heat for extended periods can degrade the product. For applications where extended use may be required, the Ultra-Drain Seal Plus should be considered.

Ultra-Spill Berm®



Temporary berm seals off spills from the environment, nearby drains, and doorways

- + Standard 10-foot sections can be cut to various lengths.
- + Unique, urethane material “weeps” into small cracks and crevices to seal off liquid flow.
- + The Ultra-Spill Berm is non-absorbing and is easily cleaned for repeated use.
- + Applications include:
 - Spill response
 - Temporary secondary containment
 - Sealing off of doorways during wash down operations
- + Flexible Ultra-Spill Berm will bend and turn to form almost any shape while temporarily “bonding” to any smooth surface.
- + Helps comply with NPDES and SPCC.



| Part# | Color | Dimensions in (mm) | Weight lbs. (kg) |
|-------|--------|--------------------------------------|------------------|
| 2100 | Orange | 120 x 4 x 2.3 (3,048 x 101.6 x 57.2) | 31.0 (14.0) |

2101 Connectors used to connect 10' sections • 2102 90° Corners used with Connectors • 2104 Carrying case



UltraTech International, Inc.
11542 Davis Creek Court, Jacksonville, Florida 32256 USA
(800) 353-1611 · 1-904-292-1611 · www.constructioncompliance.com

Scan for the full version of the Construction Compliance & Stormwater Management Catalog!

