



ULTRATECH
INTERNATIONAL, INC.

Ultra-Containment Berms®



Ultra-Containment Berm® Foam Wall Model

Low-profile design is perfect for equipment maintenance and portable drum containment

www.spillcontainment.com · (800) 353-1611 · 1-904-292-1611

Ultra-Containment Berm® Foam Wall Model

Low-profile design is perfect for equipment maintenance and portable drum containment. Low, 4" sidewall contains spills - keeps plant floors and soil free from contamination.



12' x 50' rolled up

Part#	Dimensions ft. (m) Wall Height: 4 in. (102 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8466	4 x 4 (1.2 x 1.2)	39 (148)	11.0 (5.0)
8467	6 x 6 (1.8 x 1.8)	67 (254)	19.8 (9.0)
8461	8 x 8 (2.4 x 2.4)	159 (602)	26.4 (12.0)
8470	10 x 10 (3.0 x 3.0)	249 (943)	35.3 (16.0)
8471	10 x 20 (3.0 x 6.1)	498 (1,885)	59.5 (27.0)
8477	12 x 30 (3.7 x 9.1)	897 (3,396)	120.0 (54.4)
8463	12 x 35 (3.7 x 10.7)	1,047 (3,963)	110.2 (50.0)
8464	12 x 50 (3.7 x 15.2)	1,496 (5,663)	149.9 (68.0)

Ultra-Containment Berm® Foam Wall Plus Model

Foam sidewalls are an exceptional way to provide structure to a berm's sidewalls while allowing effortless entry and exit. The removable foam supports in the Ultra-Containment Berm, Foamwall Plus Model makes replacement of old or damaged foam, quick and easy.



Copolymer 2000™ Part#	PVC 22 oz. Part#	Dimensions ft. (m) Wall Height: 4 in. (102 mm)	Containment Capacity gal. (L)	Copolymer 2000™ Weight lbs. (kg)	PVC 22 oz. Weight lbs. (kg)
8955	8963	12 x 20 (3.7 x 6.1)	598 (2,263)	235 (107)	220 (100)
8956	8964	12 x 30 (3.7 x 9.1)	897 (3,396)	245 (111)	230 (104)
8957	8965	12 x 50 (3.7 x 15.2)	1,496 (5,663)	265 (120)	250 (113)

Part#	Description	Dimensions in. (mm)	Weight lbs. (kg)
8966	Replacement Foam - 4' - 20 MIL PVC	48 x 4 x 4 (1,219 x 102 x 102)	1 (0.5)
8967	Replacement Foam - 6' - 20 MIL PVC	72 x 4 x 4 (1,829 x 102 x 102)	2 (1)

Ultra-Containment Berm® Rapid Rise Model

Sidewalls remain down during normal operations, loading and unloading. Vehicles and equipment can drive in and out from any angle. In the case of a spill, the foam ring around the top perimeter of the containment berm rises with the level of spilled liquid.



8431

Empty Berm



Filled Berm

Copolymer 2000™ Part#	PVC 22 oz. Part #	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Copolymer 2000 Weight lbs. (kg)	PVC 22 oz. Weight lbs. (kg)
8430	8654	4 x 6 (1.2 x 1.8)	179 (678)	31.0 (14.0)	24.0 (11.0)
8431	8630	6 x 6 (1.8 x 1.8)	269 (1,018)	37.0 (17.0)	30.0 (14.0)
8432	8631	10 x 10 (3.0 x 3.0)	748 (2,831)	69.0 (31.0)	54.0 (24.5)
8710	8655	12 x 12 (3.7 x 3.7)	1077 (4,077)	85.0 (39.0)	66.0 (30.0)
8437	8656	12 x 26 (3.7 x 7.9)	2,333 (8,831)	151.0 (68.5)	118.0 (54.0)
8711	8632	12 x 30 (3.7 x 9.1)	2,692 (10,190)	171.0 (78.0)	134.0 (61.0)
8712	8657	12 x 40 (3.7 x 12.2)	3,590 (13,590)	218.0 (99.0)	170.0 (77.0)
8713	8633	12 x 50 (3.7 x 15.2)	4,488 (16,989)	266.0 (121.0)	207.0 (94.0)
8714	8658	12 x 60 (3.7 x 18.3)	5,385 (20,384)	313.0 (142.0)	244.0 (111.0)
8715	8659	12 x 72 (3.7 x 22.0)	6,462 (24,461)	370.0 (168.0)	288.0 (131.0)
8716	8660	15 x 15 (4.6 x 4.6)	1,683 (6,371)	115.0 (52.0)	93.0 (42.0)
8717	8661	15 x 20 (4.6 x 6.1)	2,244 (8,495)	141.0 (64.0)	114.0 (52.0)
8718	8662	15 x 30 (4.6 x 9.1)	3,366 (12,742)	195.0 (89.0)	158.0 (72.0)
8719	8663	15 x 40 (4.6 x 12.2)	4,488 (16,989)	248.0 (113.0)	201.0 (91.0)
8433	8664	15 x 50 (4.6 x 15.2)	5,610 (21,234)	302.0 (137.0)	244.0 (111.0)
8720	8665	15 x 60 (4.6 x 18.3)	6,732 (25,483)	356.0 (162.0)	286.0 (130.0)
8434	8666	15 x 66 (4.6 x 20.1)	7,405 (28,028)	388.0 (175.0)	313.0 (142.0)
8721	8667	15 x 72 (4.6 x 21.9)	8,078 (30,579)	420.0 (191.0)	338.0 (153.0)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Ultimate Model

Drive-in/drive-out “living hinge” endwalls teamed up with collapsible sidewalls offer the ultimate combination — “Hands Free” convenience and an affordable design!



Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8505	12 x 60 (3.7 x 18.3)	5,385 (20,382)	297.0 (134.5)
8506	15 x 50 (4.6 x 15.2)	5,610 (21,234)	290.0 (131.5)
8507	15 x 66 (4.6 x 20.1)	7,405 (28,028)	369.0 (167.0)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Economy Model

Economical design offers cost savings and secure containment. L-shaped aluminum brackets provide sturdy sidewall support.



Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8250	4 x 6 (1.2 x 1.8)	179 (678)	21.0 (9.5)
8251	6 x 6 (1.8 x 1.8)	269 (1,018)	26.0 (12.0)
8252	10 x 10 (3 x 3)	748 (2,831)	52.0 (23.5)
8253	12 x 60 (3.7 x 18.3)	5,385 (20,384)	268.0 (121.5)
8254	15 x 50 (4.6 x 15.2)	5,610 (21,234)	259.0 (117.5)
8255	15 x 66 (4.6 x 20.1)	7,405 (28,028)	334.0 (151.5)

Options: Ground Tarps, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Collapsible Wall Model

The Collapsible Wall Model Containment Berm features rugged PVC sidewall assemblies for sidewall support. Simply swivel the “feet” of the PVC supports to lower or raise the sidewalls in just seconds!



Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8405	4 x 6 (1.2 x 1.8)	179 (678)	26.0 (12.0)
8403	6 x 6 (1.8 x 1.8)	269 (1,018)	32.0 (14.5)
8400	10 x 10 (3.0 x 3.0)	748 (2,831)	58.0 (26.5)
8550	10 x 20 (3.0 x 6.1)	1,496 (5,663)	96.0 (44.0)
8551	10 x 30 (3.0 x 9.1)	2,244 (8,495)	132.0 (60.0)
8552	10 x 40 (3.0 x 12.2)	2,992 (11,326)	170.0 (77.0)
8553	10 x 50 (3.0 x 15.2)	3,740 (14,157)	209.0 (95.0)
8554	12 x 12 (3.7 x 3.7)	1,077 (4,077)	69.0 (31.0)
8555	12 x 20 (3.7 x 6.1)	1,795 (6,795)	103.0 (47.0)
8556	12 x 30 (3.7 x 9.1)	2,692 (10,190)	142.0 (64.0)
8557	12 x 40 (3.7 x 12.2)	3,590 (13,590)	183.0 (83.0)
8558	12 x 50 (3.7 x 15.2)	4,488 (16,989)	224.0 (102.0)
8404	12 x 60 (3.7 x 18.3)	5,385 (20,382)	265.0 (120.0)
8559	15 x 15 (4.6 x 4.6)	1,683 (6,371)	95.0 (43.0)
8560	15 x 20 (4.6 x 6.1)	2,244 (8,495)	119.0 (54.0)
8561	15 x 30 (4.6 x 9.1)	3,366 (12,742)	164.0 (74.0)
8562	15 x 40 (4.6 x 12.2)	4,488 (16,989)	210.0 (95.0)
8401	15 x 50 (4.6 x 15.2)	5,610 (21,234)	257.0 (116.5)
8402	15 x 66 (4.6 x 20.1)	7,405 (28,028)	332.0 (150.5)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Berm® Compact Model

Compact design folds into a tight package – minimal space required to store onboard trucks and hazmat response vehicles. Sidewalls lower quickly to allow drive in/drive out.

Once sidewalls are lowered, vehicles and heavy equipment can drive in or out.



Copolymer 2000™ Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
8609	4 x 6 (1.2 x 1.8)	179 (678)	33 (15.0)
8610	6 x 6 (1.8 x 1.8)	269 (1,018)	39 (17.7)
8611	10 x 10 (3.0 x 3.0)	748 (2,831)	72 (32.7)
8680	10 x 20 (3.0 x 6.1)	1,496 (5,663)	117 (53.1)
8681	10 x 30 (3.0 x 9.1)	2,244 (8,495)	161 (73.0)
8682	10 x 40 (3.0 x 12.2)	2,992 (11,326)	206 (93.4)
8683	10 x 50 (3.0 x 15.2)	3,740 (14,157)	250 (113.4)
8684	12 x 12 (3.7 x 3.7)	1,077 (4,077)	89 (40.4)
8685	12 x 20 (3.7 x 6.1)	1,795 (6,795)	126 (57.1)
8686	12 x 30 (3.7 x 9.1)	2,692 (10,190)	173 (78.5)
8687	12 x 40 (3.7 x 12.2)	3,590 (13,590)	219 (99.3)
8688	12 x 50 (3.7 x 15.2)	4,488 (16,989)	266 (120.7)
8612	12 x 60 (3.7 x 18.3)	5,385 (20,384)	313 (142.0)
8689	15 x 15 (4.6 x 4.6)	1,683 (6,371)	118 (53.5)
8690	15 x 20 (4.6 x 6.1)	2,244 (8,495)	143 (64.9)
8691	15 x 30 (4.6 x 9.1)	3,366 (12,742)	194 (88.0)
8692	15 x 40 (4.6 x 12.2)	4,488 (16,989)	245 (111.1)
8613	15 x 50 (4.6 x 15.2)	5,610 (21,234)	296 (134.3)
8614	15 x 66 (4.6 x 20.1)	7,405 (28,028)	378 (171.5)

Part# 8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts)

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand

Ultra-Containment Wall®

Modular, hard-walled system provides long-term, high-capacity spill containment



Part#	Wall Height & Description	Dimensions in. (mm)	Weight (lbs. (kg))
8760	1 ft. (0.3 m) - Straight Section	120 x 12 x 12 (3,048 x 305 x 305)	33.0 (15.0)
8761	1 ft. (0.3 m) - Corner Section	22 x 22 x 12 (559 x 559 x 305)	9.0 (4.0)
8762	2 ft. (0.6 m) - Straight Section	100 x 24 x 24 (2,540 x 610 x 610)	70.0 (32.0)
8763	2 ft. (0.6 m) - Corner Section	35 x 30 x 24 (889 x 762 x 610)	26.0 (12.0)
8764	3 ft. (0.9 m) - Straight Section	72 x 24 x 36 (1,829 x 610 x 914)	60.0 (27.5)
8765	3 ft. (0.9 m) - Corner Section	30 x 30 x 36 (762 x 762 x 914)	36.0 (16.5)
8770	30 ml Textured Polyethylene Liner	Custom (per sq. ft./m)	20 oz/sq yd (0.57 kg/sq yd)

Ultra-Containment Berm® Mini Foam Wall Model

Foldable mini berms (duck ponds) are compact and easy to store but deploy in a moment's notice to respond to a spill. Berms fold down and can be secured using attached strap – provides simple and convenient transport and storage.



Part#	Material of Construction	Dimensions ft. (m) Wall Height: 6 in. (152 mm) Wall Thickness: 2 in. (51 mm)	Containment Capacity gal. (L)	Weight (lbs. (kg))
8850	22 oz. PVC	2 x 2 (0.6 x 0.6)	15 (57)	3 (1.5)
8845	22 oz. PVC	3 x 3 (0.9 x 0.9)	33.7 (128)	5 (2.3)
8852	22 oz. PVC	4 x 4 (1.2 x 1.2)	60 (227)	7 (3.0)
8854	22 oz. PVC	4 x 6 (1.2 x 1.8)	75 (284)	9 (4.0)
8846	22 oz. PVC	5 x 5 (1.5 x 1.5)	93.5 (354)	9 (4.1)
8847	22 oz. PVC	6 x 6 (1.8 x 1.8)	134.7 (510)	12 (5.4)

Ultra-Containment Berm® Modular Model (Gorilla Berm)

Modular construction allows containment areas of any size to be configured. Triangular-shaped, polymer-coated foam support blocks (72"L x 16"W x 6"H) are used with rebar (not included) to provide sidewall structure. Molded-in slots in top of foam blocks hold rebar - secures material in place. Standard material is a 22oz., anti-skid, coated vinyl fabric.



8748
Modular side walls are easily placed into any configuration during setup.

Part#	Description	Dimensions in. (mm)	Weight (lbs. (kg))
8730	Modular Model Side Wall	72 x 18 x 6 (1828.8 x 457.2 x 152.4)	19 (8.6)
8731	Modular Model Corner Wall	24 x 24 x 6 (609.6 x 609.6 x 152.4)	9 (4.1)
8734	Modular Model Liner - Custom PVC Textured 24 oz. Black	-	-

Ultra-Wellhead Berm®

Captures, collects and contains drips and spills that come from wellheads. Engineered to provide complete (360°) protection.



Part#	Desc.	Material	Wall Height in. (mm)	Outside Dimensions ft. (m)	Inner Opening Inside Dims. in. (mm)	Containment Capacity gal. (L)	Weight (lbs. (kg))
8856	Wellhead Berm	Copolymer 2000™	4 (102)	10.5 x 10.5 (3.2 x 3.2)	24 x 24 (610 x 610)	217 (821)	51.0 (23.0)
8858	Wellhead Berm w/ Hood	Copolymer 2000™ & 22oz. PVC (Hood)	4 (102)	10.5 x 10.5 (3.2 x 3.2)	24 x 24 (610 x 610)	217 (821)	63.0 (28.5)



All Ultra-Containment Berms meet EPA 40 CFR 112 (SPCC) and EPA 40 CFR 264.175 spill containment regulations. Custom materials and sizes available.



11542 Davis Creek Court, Jacksonville, Florida 32256 USA
(800) 353-1611 · 1-904-292-1611 · 1-904-292-1325 fax
spillcontainment.com · info@spillcontainment.com